



Our exclusive Optiview speed dome cameras allow you to pan, tilt, or zoom up to 220X. With a crystal clear image day or night and a full OSD allowing access to all functions - it can't be beat at this price!

Note: To use a PTZ camera on our PC-Based DVRs, you must have an RS485 Converter.

### **Product Includes**

- Wall Bracket
- Heater / Blower
- Power supply
- Installation / Instruction Manual
- Free technical support

### **Features**

- 22X Optical Zoom
- 10X Digital Zoom
- On Screen Display menu

- 127 Presets
- Patterns: 8 patterns, 20 presets per pattern
- Indoor / Outdoor
- Aluminum Construction
- Day / Night

## Specifications

<b>Image sensor:</b>	1/4" Super HAD SONY CCD
<b>Horizontal Resolution:</b>	480 TV Lines (Color), 570 TV Lines (B/W night mode)
<b>Pan Angle:</b>	360° continuous pan rotation
<b>Pan Speed:</b>	0.1-180° /s
<b>Tilt Speed:</b>	15-60° /s
<b>Pixels:</b>	768 x 494
<b>SN Ratio:</b>	> 50db
<b>Gain Control:</b>	Auto/Manual
<b>Back Light Compensation:</b>	Auto/Manual
<b>Optical Zoom:</b>	22X
<b>Digital Zoom:</b>	10X
<b>Lens:</b>	4 ~ 86mm, F1.6
<b>Preset Positions:</b>	127
<b>Comm Port:</b>	RS485 Pelco-D, Pelco-P selectable
<b>Operating Temperature (without blower):</b>	0C ~ 50C (22F ~ 122F)
<b>Operating Temperature (with blower):</b>	-50C ~ 60C (-58F ~ 140F)
<b>Power Supply:</b>	12VDC (included)
<b>Power Consumption:</b>	30W (with fan/heater)